

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problems Mailbox.**

**THIS PAGE BLANK (USPTO)**

# (12) UK Patent Application (19) GB (11) 2 343 531 (13) A

(43) Date of A Publication 10.05.2000

(21) Application No 9911511.5

(22) Date of Filing 19.05.1999

(30) Priority Data

(31) 09082022 (32) 20.05.1998 (33) US

(71) Applicant(s)

Datalogic Corporation  
(Incorporated in USA - Michigan)  
4595 Broadmoor S.E., Suite 140, Grand Rapids,  
Michigan 49512, United States of America

(72) Inventor(s)

Jeffrey Alan Schanhals  
Stephen Michael Cole  
George William Vallillee IV

(74) Agent and/or Address for Service

Barker Brettell  
138 Hagley Road, Edgbaston, BIRMINGHAM,  
B16 9PW, United Kingdom

(51) INT CL<sup>7</sup>

G06F 1/00, H04L 12/24

(52) UK CL (Edition R)

G4A AAP

(56) Documents Cited

GB 2296584 A WO 93/21581 A US 5479408 A  
Infoworld, v14, n21, page 45, 25 May 1992, ISSN:  
0199-6649

(58) Field of Search

UK CL (Edition R) G4A AAP AFL  
INT CL<sup>7</sup> G06F 1/00 17/60, H04L 9/32 12/24  
Online: WPI, EPODOC, PAJ, INSPEC, COMPUTER

(54) Abstract Title

**Supporting a worker in a distributed work environment**

(57) A distributed work environment in which a plurality of mobile workers using portable computing devices (16) can gain access to a network (11) via network access stations (18a-c) installed within the work environment. Each network access station (18) is associated with a physical location (20a-c) within the work environment and includes a unique station identifier (19a-c) that may be associated with the physical location. Upon connection to the network (11), the unique station identifier (19) is provided to a location/association system (14) on the network. Based on the unique station identifier (19) the location/association system (14) provides the worker associated with the computing device (16) access to privileges and services associated with the physical location. The computing device may also provide to the location/association system (14) a unique device identifier (17) associated with the computing device and/or the worker's identity. Based on the unique device identifier (17), the location/association system (14) may provide additional privileges and services in accordance with the worker's specified preferences.




FIG. 1






FIG. 1

FIG. 2








FIG. 3

FIG. 4A

VOYAGER COMMAND BAR		PICKUP HOLD CONFERENCE TRANSFER FORWARD AD HOC		ABC DEF 1 2 3 GHI JKL MNO 4 5 6 PQR TUV WXYZ 7 8 9 * OPER # 0		NAME	NUMBER	TIME	ARRIVAL	LOCAL	REMOTE	MONITOR
<div>TELEPHONY</div> <div>MESSAGING</div> <div>COLLABORATION</div> <div>INTERNET</div> <div>ENVIRONMENT</div>												SPEED DIAL

VOYAGER COMMAND BAR		BRAKE, JEFF KOFF'S, CHAD AND CAR				NAME	NUMBER	TIME	ARRIVAL	LOCAL	REMOTE	MONITOR
<div>TELEPHONY</div> <div>MESSAGING</div> <div>COLLABORATION</div> <div>INTERNET</div> <div>ENVIRONMENT</div>												SPEED DIAL

FIG. 4B



FIG. 4C

VOYAGER COMMAND BAR		TELEPHONY		MESSAGING		COLLABORATION		INTERNET		ENVIRONMENT		VOICE	
AUDIX TOOLS ▷ PLAY ▷ FAST FWD ◁ PREV ◁ REWIND X DELETE ◁ STOP ◁ SAVE ▷ NEXT		FROM		ANI		SUBJECT		TIME		DATE		LEN...	
AUDIX MESSAGES		PAULEN, SUZANNA		5604803		PATENT DOCU..		1:04 PM		MARCH 16,..		41 SEC	
		BECK, JOHN		2904551		NEW SOFTWARE..		1:04 PM		MARCH 16,..		60 SEC	
		MURPHY, LESLIE		4403959		COMING SOON..		1:04 PM		MARCH 15,..		32 SEC	
		TANNER, JAMES		2103204		SILK SCREEN O..		1:04 PM		MARCH 15,..		47 SEC	
		PRATT, PAUL		5414327		GLASS ORDER..		1:04 PM		MARCH 14,..		26 SEC	
		DEKKER, SCOTT		2134556		LAPTOP STATU..		1:04 PM		MARCH 13,..			
		KURTZ, JEFFREY		4983025		BOARD MEETI..		1:04 PM		MARCH 13,..		21 SEC	

VOYAGER COMMAND BAR		TELEPHONY		MESSAGING		COLLABORATION		INTERNET		ENVIRONMENT		VOICE	
EMAIL FOLDERS [D] DATALOGIC [D] NEWS FOLDER [D] ANCHORDESK [D] CNN [D] MSNBC [D] POINT CAST [D] PERSONAL FOLDER [D] PUBLIC FOLDER		FROM		SUBJECT		RECEIVED		SIZE					
EMAIL MESSAGES		WINQUIST, BRETT		RETURN CALL FROM TONY		1/5 /98 3:18 PM		3K				E-MAIL	
		MIME :RICK.ROBERTS@..		CONFIGURATION MANAGEMENT		1/6 /98 2:45 PM		329K				PAGING	
		MIME :CMORTELLARO@LE..		HERE IS THE SPREADSHEET		1/6 /98 4:26 PM		55K					
		PC :ANCHORDESK@ISLISTS..		FUTURE OF SOFTWARE REVEALED		1/7 /98 8:03 AM		8K					


FIG. 4D

FIG. 4E

VOYAGER COMMAND BAR		PAGER TOOLS		PAGER MESSAGES		FROM		MESSAGE		RECEIVED		VOICE	
		SEND				WHEELER, DENNIS		CALL ME IF YOU GET BACK TO THE OFFICE???		1/11/98 4:13 PM		E-MAIL	
						GORDAN, DEAN		CALL ME AT 512-3902		1/11/98 9:27 PM		PAGING	
						POTTER, DOUGLAS		IRDA COMMITTEE MEETING WILL BE HELD AT THE CONFER...		1/11/98 1:39 PM			
						SMIT, JOHN		NEW NOTEBOOK FOR HEWLETT PACKARD WITH 4 MEGA...		1/12/98 4:21 PM			
						SMITH, DEREK		NEED TO GET A QUOTE FOR THE PARTS THAT YOU REQUESTED		1/12/98 7:03 AM			
TELEPHONY		MESSAGING		COLLABORATION		INTERNET		ENVIRONMENT					

7 / 16

VOYAGER COMMAND BAR		IIS.USDATALOGIC.COM		CONNECTIONS		CONNECTION	
AVAILABLE		✓ AREA		DESCRIPTION		APPLICATION	
CHRIS STEFFES						FILE	
SUZANNE PAULEN						VIDEO	
						CHAT	
TELEPHONY		MESSAGING		COLLABORATION		INTERNET	
						ENVIRONMENT	



CHRIS STEFFES

FIG. 4F

FIG. 4G

VOYAGER COMMAND BAR		<input checked="" type="checkbox"/> APPLICATION		<input type="checkbox"/> CONNECTION
AVAILABLE <input checked="" type="checkbox"/> C:\MY DOCUMENTS \ DESKTOP \ BACKUP TEST FOLDER <input checked="" type="checkbox"/> C:\MY DOCUMENTS \ DESKTOP \ BITMAPS <input type="checkbox"/> COLLABORATION CONNECTION - PAINT INBOX - MICROSOFT EXCHANGE <input type="checkbox"/> REGISTRY EDITOR <input type="checkbox"/> VOYAGER COMMAND BAR				
TELEPHONY		MESSAGING	COLLABORATION	INTERNET
		ENVIRONMENT		
APPLICATION FILE VIDEO CHAT				

8 /16

VOYAGER COMMAND BAR		LOCAL		REMOTE			
		<input type="checkbox"/> SHOW    PAUSE <input type="checkbox"/> TOP		<input type="checkbox"/> SHOW    PAUSE <input type="checkbox"/> TOP			
TELEPHONY		MESSAGING	COLLABORATION	INTERNET	ENVIRONMENT		
		CONNECTION					
		APPLICATION					
		FILE					
		VIDEO					
		CHAT					

FIG. 4H

FIG. 4I


VOYAGER COMMAND BAR		SEND				↑ AUTO ^ SEND &v TO X CLEAR		RECEIVED		INFO IMAGE FW IDEODATALOGIC CALL VIDEO RP32_50 STATS		NSPLAY VIDEO CHAT		CONNECTION APPLICATION FILE VIDEO CHAT	
TELEPHONY		MESSAGING		COLLABORATION		INTERNET		ENVIRONMENT							

9 / 16

FIG. 4J

VOYAGER COMMAND BAR		SEND		THIS IS A MESSAGE TO TEST THE CHAT CHANNEL		^ SEND &v TO X CLEAR		RECEIVED		MESSAGE HELLO HELLO TO YOU!!!		FROM SELF CHRIS		CONNECTION APPLICATION FILE VIDEO CHAT	
TELEPHONY		MESSAGING		COLLABORATION		INTERNET		ENVIRONMENT							

FIG. 4K



10 / 16

FIG. 4L





FIG. 4M



11 / 16




FIG. 4N

FIG. 40

VOYAGER COMMAND BAR		SHOW TIME		ON VIDEO RGB		INPUT OFF SCREEN LANGUAGES		AUDIO SETTINGS		<> PICTURE <> PHASE <> APPLY		<> BRIGHT <> H POS <> V POS		<> RED <> RESET <> SETTINGS		<> GREEN <> CLOCK <>		PROJECTORS SCREENS LIGHTING BLINDS VCR HVAC
TELEPHONY				MESSAGING		COLLABORATION		INTERNET		ENVIRONMENT								

VOYAGER COMMAND BAR		LEFT SCREEN		< UP > DOWN < STOP		CENTER SCREEN		< UP > DOWN < STOP		RIGHT SCREEN		< UP > DOWN < STOP		<> BRIGHT <> H POS <> V POS		<> RED <> RESET <> SETTINGS		<> GREEN <> CLOCK <>		PROJECTORS SCREENS LIGHTING BLINDS VCR HVAC
TELEPHONY				MESSAGING		COLLABORATION		INTERNET		ENVIRONMENT										

FIG. 4P

FIG. 4Q


VOYAGER COMMAND BAR		OUTER LIGHTS <input type="checkbox"/> ON <input type="checkbox"/> OFF <input type="checkbox"/> BRIGHTEN <input type="checkbox"/> DIM		INNER LIGHTS <input type="checkbox"/> ON <input type="checkbox"/> OFF <input type="checkbox"/> BRIGHTEN <input type="checkbox"/> DIM		CENTER LIGHTS <input type="checkbox"/> ON <input type="checkbox"/> OFF		PROJECTORS SCREENS LIGHTING BLINDS VCR HVAC	
TELEPHONY		MESSAGING		COLLABORATION		INTERNET		ENVIRONMENT	

FIG. 4R

VOYAGER COMMAND BAR		LEFT BLINDS <input type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> STOP		CENTER BLINDS <input type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> STOP		RIGHT BLINDS <input type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> STOP		PROJECTORS SCREENS LIGHTING BLINDS VCR HVAC	
TELEPHONY		MESSAGING		COLLABORATION		INTERNET		ENVIRONMENT	



FIG. 4S



14 / 16





FIG. 4T

FIG. 4U



15 / 16




FIG. 4V




FIG. 4W




FIG. 4X

SYSTEM AND METHOD FOR SUPPORTING A  
WORKER IN A DISTRIBUTED WORK ENVIRONMENT

FIELD OF THE INVENTION

5 The present invention relates generally to a  
system and method for supporting a worker in a  
distributed work environment. In particular, the present  
invention relates to a system and method that identifies  
and locates a worker in a distributed work environment  
when a data communication connection is established  
10 between the worker's computing device and a network and  
that provides the worker with services and privileges  
based on the worker's location and/or identity.

BACKGROUND OF THE INVENTION

15 In recent years, the use of portable data  
communication devices has become commonplace and even  
necessary in the work environment. Workers must often  
travel from their offices and yet must retain  
connectivity to the workplace to access their workfiles  
and to respond to communications from others. Portable  
20 data communication devices, such as laptop computers,  
wireless telephones and pagers, facilitate travel outside  
of the workplace by enabling the mobile worker to  
maintain access to workfiles, such as via a modem or  
wireless link to a wired local area network (LAN), and to  
25 respond to communications from others, such as by e-mail,  
wireless telephone or pager.

Even within the work environment itself,  
workers often move about freely to attend meetings or to  
engage in conferences with co-workers. Yet, for a worker  
30 to retain connectivity to the workplace while moving  
about within the workplace, the worker must transport  
much of the same burdensome baggage as if he were  
traveling away from the workplace: a laptop computer, a  
pager, and perhaps even a wireless telephone, and  
35 possibly even a collection of wires and connectors. In

addition, to gain access to the LAN, the internally mobile worker must find an available access port to establish a communications link, which may be difficult in conference rooms or offices where more than one user wants to connect. Thus, the worker may not be able to gain access to workfiles or presentation programs that would be useful when communicating to co-workers, or, if borrowing an access port assigned to another person, the mobile worker may not be able to access coded files or other privileges that have been tailored to the mobile worker's needs or that are available at particular areas within the work facility. Also, a worker who is often absent from his designated work space may miss important communications from others, such as phone calls, because the worker cannot be located within the work facility.

Although solutions are known which address the foregoing problems, the solutions are not complete or introduce other complications. For example, to ensure that a mobile worker receives incoming communications, one known solution includes a public address system for paging the worker. Other more sophisticated solutions include systems that locate mobile workers within the work environment through the use of a network of wireless transmitters, such as badges worn by the worker, and receivers that may be mounted in fixed locations throughout the work facility. Once the individual's location has been determined, such systems may, for example, automatically route telephone calls to the telephone nearest the individual's location. Additionally, such systems may provide the individual with certain privileges, such as access to restricted work areas or customized automatic control of the environment in particular work areas. However, it would be desirable to provide the individual with even greater freedom to move about the workplace. Such freedom would include providing customized access to the facility's LAN or other data communications network, such that the

worker's office virtually accompanies the worker throughout the work facility.

5           The possibility of establishing a virtual office is facilitated by the widespread use of computers in the workplace, e.g. laptops and other portable or desktop computers and workstations, which allow an individual to access multiple information service applications such as e-mail, voicemail, word processing, internet access and telephony services via the work  
10       facility's LAN. More and more of these types of information applications are being accessed by individuals via their personal computers, and more and more individuals are carrying computing devices or other types of data communication devices with them, including  
15       "notebook" computers, complex calculators, daily planners, personal digital assistants, electronic address books, etc. Without the ability to access the information applications from remote locations, valuable time and resources are spent running back to the office, or relocating to a location that has a wired LAN access.  
20

          Thus, it would be desirable to provide a more elegant solution to these problems than offered by known solutions. Such a solution would allow a worker to move freely about the work facility without hindering access  
25       to wired systems. Such a solution also would be capable of locating the worker within the work facility such that communications can be automatically routed to the worker and such that the worker may enjoy certain customized privileges regardless of the worker's location or take  
30       advantage of other privileges or services available only at particular locations. Further, such a solution would provide this freedom of movement and unrestricted enjoyment of privileges without the need for installation of a costly network of transmitters and receivers which  
35       serve the sole purpose of locating mobile workers. Instead, the location feature of the solution would be integrated with the other system features. Thus, it would be advantageous to provide a system and method for

supporting a worker in a distributed work environment which allows mobile access of a computing device to customized privileges and services based on the user's identification information and/or the physical location of the user.

#### SUMMARY OF THE INVENTION

The present invention relates to a method of supporting a worker using a computing device in a distributed work environment with a plurality of physical locations having a plurality of network access stations connected to a network so that the computing device may be connectable to the network at a network access station associated with a physical location within the work environment. The method may include positioning a communications port of the computing device near a communications transceiver of the network access station to establish a communications data link between the computing device and the network access station; establishing a network connection between the computing device and the network at the network access station to provide the computing device with a communication link to the network; registering the computing device on the network according to a network physical address associated with the network access station; determining an identity given by the worker associated with the computing device; determining the physical location of the worker associated with the computing device; providing the worker associated with the computing device with privileges and services associated with the physical location; providing the worker associated with the computing device with privileges and services associated with the identity of the worker.

The present invention also relates to a data communications system for supporting a worker using a computing device in a distributed work environment with a plurality of physical locations having a plurality of network access stations connected to a network so that

the computing device is connectable to the network at a network access station associated with a physical location within the work environment. The system includes means for registering the computing device on the network according to a network physical address associated with the network access station, means for determining an identity given the worker associated with the computing device, means for determining the physical location of the worker associated with the computing device, means for providing the worker associated with the computing device with privileges and services associated with the physical location, and means for providing the worker associated with the computing device with privileges and services associated with the identity of the worker.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention will hereafter be described with reference to the accompanying drawings, wherein like reference numerals denote like elements, and:

FIG. 1 is a block diagram of a system for supporting a worker in a distributed work environment according to a preferred embodiment of the present invention;

FIG. 2 is a flowchart representation of a method for supporting a worker in a distributed work environment according to a preferred embodiment of the present invention;

FIG. 2A is a flowchart representation of several steps of the method of FIG. 2 showing greater detail thereof;

FIG. 3 is a chart indicating exemplary applications operable via a portable computing device as part of the system depicted in FIG. 1; and

FIGS. 4A-4X are user interface screens for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention.



**DETAILED DESCRIPTION OF  
PREFERRED AND ALTERNATIVE EMBODIMENTS**

Referring to FIG. 1, there is shown a block diagram of a system for supporting a worker in a distributed work environment according to a preferred embodiment of the present invention. A distributed work environment is meant to include any work environment in which a worker who migrates between work locations within a facility may access data, application programs, electronically controlled appliances or peripheral devices, etc. based on the services and devices available at a particular location and/or the privileges accorded the worker and/or the preferences defined by the worker. The distributed work environment may be implemented by a system 10 which includes a local area network (LAN) 11 (e.g., an Ethernet LAN or other network using other protocols) that interconnects a plurality of communication nodes. LAN 11 includes one or more network servers 12 for managing communications on the network among the plurality of communication nodes to which a wide variety of computing and other communication devices may be linked.

System 10 includes an infranet positioning system (IPS) 14 which may be a software application program resident on network server 12 or which may be on a separate server in system 10, one or more portable computing devices 16, and a plurality of network access stations 18a-c which provide for a network connection between computing devices 16 and LAN 11. IPS 14, computing devices 16, and network access stations 18a-c cooperate to identify the physical location of computing device 16 based on a physical location 20a, 20b or 20c associated with the network access station 18a, 18b or 18c in communication with device 16. IPS 14 performs a variety of detection and association functions, which will be described in detail below. Physical locations 20a-c preferably are defined by walls, freestanding

panels, furniture systems, etc. and may include different offices, conference rooms, or work spaces, areas or locations in a building or in a set of adjacent or remotely located buildings associated with a work facility.

Portable computing device 16 may be a portable computer such as a laptop computer, notebook computer, electronic calculator, personal digital assistant, or other electronic device having an infrared or other wireless or wired communication port 22 for communications with network access stations 18a-c. In the preferred embodiment, communication port 22 is an infrared data port that is compliant with the standards of the Infrared Data Association<sup>SM</sup> (IrDA) (e.g., "Infrared Data Association Serial Infrared Link Access Protocol (IrLAP)", Version 1.0, June 23, 1994, or any subsequent or related standard). Computing device 16 further includes a unique identifier 17 to identify the computing device and/or the worker associated with that computing device. For example, computing device 16 may be identified by the "device name" that is assigned to device 16 when device 16 is originally configured (e.g., by a system administrator for the LAN). The user may be identified by the user's "login name" which, for example, may be selected by the user when setting up device 16 or which may be assigned by a system administrator. Thus, the device name portion of unique identifier 17 is fixed. However, the portion of unique identifier 17 that identifies the worker may vary in situations in which more than one worker uses the particular portable computing device 16.

Network access stations 18a-c, which enable communications between computing device 16 and LAN 11, are associated with each physical location 20a-c. Stations 18a-c may be physically located at physical locations 20a-c or may be remotely located but accessible at locations 20a-c via a wired or wireless connection. Stations 18a-c include a network physical address (NPA)

19a-c, such as the unique identifier code associated with or stored on each network interface card (e.g., typically by the manufacturer), to identify the particular station 18. However, it should be understood that NPA 19 may be any type of unique tag or label than can be used to identify a particular station 18. Network access stations 18a-c may take the form of a communications card or other electronic card or may be a docking station having one or more microprocessors or other controllers for performing intelligent operations according to a control program or other program-defined routines. Stations 18a-c include communication transceivers or interfaces 24a-c for communications with computing device 16. Interfaces 24a-c may be infrared transceivers or other wireless or wired communication interfaces which implement communications according to defined standards, such as the IrDA or IEEE 802.3 standards, or other commercial protocols, such as the Ethernet protocol.

With system 10, a plurality of mobile workers (not shown) carrying portable computing devices 16 can each gain access to LAN 11 either at any of different locations 20a-c or at a single location, e.g. 20a. Upon connection to LAN 11 via a network access station 18, IPS 14 can identify the worker and/or the worker's computing device 16 based on the device's unique identifier 17 and the worker's location 20 based on the NPA 19 of the network access station 18.

System 10 may also include other communication devices or systems located at or associated with each physical location 20a-c. Such devices or systems include printers 26a-c, graphics display systems 28a-c, telephones 30a-c and various environmental systems. The environmental systems are controlled by an environmental control server 32 in communication with LAN 11 and include heating, ventilating and air conditioning (HVAC) systems 34a-c, lighting systems 36a-c, appliances 38a-c (e.g., video cassette recorders, projectors, projector screens, blinds or shades, etc.) and security systems

40a-c. Telephones 30a-c are controlled by, for example, a PBX central telephone switch 42 coupled to both a public switched telephone network (PSTN) external telephone line 44 and a telephony server 46 that is in communication with LAN 11. System 10 may also include a graphics server 48 in communication with LAN 11. System 10, however, is not dependent on the communication devices and systems enumerated above, but may include a wide variety of more or fewer devices, systems and equipment depending on the work environment needed.

According to any preferred embodiment, the environmental control server may be a controller or computing device configured to control any type of appliance, which would include (but would not be limited to) audio and/or video systems or equipment, other multimedia systems equipment, conferencing equipment, presentation equipment (e.g. white board), even consumer appliances, or the like. The type of the appliances in a particular application will, of course, depend upon the nature of the environment. However, it should be recognized that a wide variety of appliances may be supported according to alternative embodiments.

Referring now to FIG. 2, there is shown a flowchart representation of a method for supporting a worker in a distributed work environment according to a preferred embodiment of the present invention. Initially, the worker enters location 20a with computing device 16 and positions device 16 near network access station 18a (step 100). Device 16 may be placed, for example, on a work surface provided by an article of furniture such as a desk, conference table or other supporting surface. Device 16 is placed sufficiently close to station 18a so that the two may communicate, preferably via an infrared data link 49. Alternatively, computing device 16 may be physically connected to network access station 18a such that communications occur via a wired data link. In any event, once device 16 is linked either physically or electronically to station

18a, station 18a may establish a network connection to LAN 11 (step 102), either automatically or in response to instructions entered by the user into computing device 16.

5                   Once a network connection is established, device 16 provides IPS 14 with relevant identification information (step 104) such that IPS 14 can perform its location and association functions and thus provide the worker with particular services and privileges. The  
10                   terms "services" and "privileges" are intended to have their broadest meanings to include, for example, any services that are under the direct or indirect control of devices, systems or equipment associated with LAN 11 and/or rights to control such devices, systems or  
15                   equipment and/or to retrieve or exchange information therefrom through application programs, interface or control routines, or in any other manner. The relevant identification information includes NPA 19 which computing device 16 retrieves from network access station  
20                   18 and provides to IPS 14. The relevant identification information further includes unique identifier 17 which, as discussed above, may include the device name and the login name of the user of device 16. Thus, computing device 16 also provides unique identifier 17 to IPS 14.

25                   Having been provided the identification information, IPS 14 may now perform its association and location functions by referring to data stored in various databases 50-64 accessible to IPS 14 (see FIG. 1). For example, in the preferred embodiment, IPS 14 may access a  
30                   database that associates each NPA 19 with a particular physical location 20 in the work facility. IPS 14 also may access a database that associates the device name portion of unique identifier 17 with a particular configuration of device 16, including available software  
35                   applications. Once the physical location and the device name of computing device 16 are known, IPS 14 can provide the worker with privileges or services (e.g., call forwarding, environmental control, etc.) that are

available at the particular physical location 20 and that are compatible with the configuration of device 16 (step 110). If a worker identification is also provided in unique identifier 17, IPS 14 may consult a database that associates the worker identification with more privileges or services available for that worker and individual preferences (e.g., environmental control settings, customized greetings, etc.) of the worker (step 112). The term "preferences" is meant to include any user-selectable or other type of configuration or setting for the interface, status, control, etc. of a device, system or equipment associated with LAN 11.

A preferred embodiment of the above method will now be described in greater detail with respect to FIG. 2A. After device 16 is positioned near and connects with network access station 18a (step 100), a connection to LAN 11 is automatically attempted (step 114). If the network is not available, the applications on computing device 16 are notified (step 116) so that the applications can adjust their operation accordingly, e.g. by disabling certain functions that require network access, etc. Next, device 16 continues periodically checking for availability of the network (step 114). Thus, once the network becomes available, a network connection may be established.

After establishment of a network connection, computing device 16 checks if the network has one or more IPSs 14 (step 118). In one embodiment, an information location service (ILS) may exist on the network which is configured to provide a list of all available and existing IPSs. Multiple IPSs may be useful, e.g. for assigning one IPS to a "zone" of several locations 20a-c in order to reduce network traffic. If no IPS 14 exists, the applications on device 16 are notified (step 120) so that the applications can adjust their operations accordingly. In the embodiment illustrated in FIG. 2A, device 16 is incapable of performing network operations in the absence of at least one IPS 14; therefore, the

routine illustrated in FIG. 2A terminates if no IPS 14 exists. In alternative embodiments, computing device 16 could operate in a "no IPS" mode in which location and association functions are not available but certain other network operations are. If one or more IPSs 14 exist, a list of the possible IPSs on the network is provided to computing device 16 (step 122).

Next, computing device 16 retrieves NPA 19 from the network access station 18 with which device 16 is in communication (step 124). As discussed above, NPA 19 may be the address of a network adapter card which is stored in the card's BIOS. In alternative embodiments, NPA 19 may be any type of unique identifier that has been assigned to network access station 18a.

NPA 19 is sent by computing device 16 to all IPSs 14 (step 130) on the network. Once an IPS 14 receives the NPA, it first determines if the NPA is one that is registered (step 132) by comparing the NPA received to a database of registered NPAs. If the NPA received is not among the list of registered NPAs, then the device having the NPA is an unauthorized device that is not allowed to communicate with IPS 14. Therefore, IPS 14 terminates communication with the device (step 134), reports to the network that the device NPA is an unidentified one (step 136), and computing device 16 notifies its applications (step 138) that it does not have access to IPS 14 so that the applications can adjust accordingly. Alternatively, IPS 14 may allow computing device 16 to register with IPS 14. In such a case, IPS 14 will request information from the user of device 16 such that available privileges and services may be associated both with the particular user and the particular device 16. Or, IPS 14 may simply provide default privileges and services.

If NPA 19 is registered, then IPS 14 adds this NPA to a table (step 140). This table is a dynamic, cross-referenced table including records for all devices 16 on the network at any given time. IPS 14 builds the

table when device 16 sends its NPA 19 to IPS 14 by gathering select information from databases 50, 52, 54, 56, 58, 60, 62 and 64. IPS 14 also reports the physical location 20 back to computing device 16 and also to other communication nodes on the network that may require this information, e.g. telephone, printer and HVAC nodes at that physical location 20 (step 142).

After IPS 14 knows the identity of the worker and the physical location 20 of device 16, IPS 14 may initiate an association process by providing the worker with privileges and services associated with the worker (FIG. 2, steps 110 and 112), provided the worker has a profile stored in the database. These privileges and services are obtained preferably by reference to one or more of the databases shown in FIG. 1, or alternatively could be stored in some other type of memory for access by IPS 14. If IPS 14 is unfamiliar with the worker and the worker's preferences and privileges, these preferences and privileges may need to be entered upon first registering the worker. This can be done by automatically establishing a set of default settings, by the worker entering the settings via computing device 16, or by some combination thereof.

The databases in FIG. 1 together comprise a reconfigurable database 65 and may include a network database 50 for storing network access point information, a telephony database 52 for storing worker and physical location information regarding telephone options and preferences, a locations database 54 for maintaining a list of all possible locations 20a-c and perhaps for maintaining a list of all available services associated with each physical location, a greetings database 56 for storing a plurality of greetings that can be recalled for a selected worker at a selected location 20a-c, a PBX gateway database 58 for using computing device 16 as a telephone, an environmental controls database 60 for storing data regarding various select environmental preferences and conditions (e.g., HVAC system settings,



control of projectors, screens, VCRs, blinds, shades, etc.) based on worker identifier 17 and/or location 20a-c, and one or more other databases 64 for holding other data such as other worker preferences having a series of privileges and preferences associated with the given identity of the worker. The worker may modify these preferences once a network connection is established. When a worker leaves the network and returns at a later time, these preferences may be saved for future recall.

More or fewer of the above databases may be part of reconfigurable database 65 in various other embodiments of the present invention. All of the above database information can be recalled by cross-referencing the information with the worker's identity, the identity of the worker's computing device, and/or the physical location of the worker.

The system and method of the present invention thus provide countless features and functions available to support a worker in a distributed work environment. For example, a worker may have telephone calls routed to a selected telephone set at a remote location, or directly to the worker's device at that location. Additionally, network communications, including electronic mail, peripheral device connections, application programs and database access for the worker may all be accessed from remote locations once a network connection is established with IPS 14. The worker may also be provided with the ability to control environmental systems including lighting, HVAC, appliance and security settings based on both individual preference and work location. The IPS continuously updates the databases to maintain the privileges and services associated with each physical location for each individual worker. In addition, the worker may be apprised of, e.g. the nearest telephone, printer, graphics display or other network service as well as its physical location within the work environment. Further, a telephone call intended for a worker may be routed

directly from a central telephone network to the actual location of the worker and received either at a telephone at the worker's location, or through the worker's computing device 16.

FIG. 3 is a chart indicating exemplary applications operable via a user interface (e.g., a command bar) accessible at a portable computing device as part of the system depicted in FIG. 1. When the worker has established a network connection and provided the relevant identification information to IPS 14, the worker operates through a series of "pull-down" menus (see, e.g. FIG. 4A) to select from the multitude of information, voice, video and communications services and privileges that may be accessed from the remote location. The worker enters commands and receives data through a command bar 150. Through command bar 150, a voice messaging object 152, e.g. AUDIX, may be accessed to retrieve, send, forward and save voicemail messages. Telephony services may also be accessed via a telephony object 154, e.g. CTI (computer telephony integration) system. According to the exemplary embodiment indicated in FIG. 3, CTI system 154 provides an interface for, among other systems and applications, any conventional telephony and telephony server systems, for example, a TSAPI-compliant telephony system (e.g. a central telephone switch/PBX of a type available from Lucent, Rolm, Northern Telecom, or any other suitable supplier, accessed through an interface shown as a PBX Gateway, with a compatible telephony server accessed through a suitable interface, or TSAPI) and/or a TAPI-compliant service provider (which may be connected through a suitable interface 170 to a TAPI-enabled application or system 166). CTI system 154 may also be connected to a multimedia data communication system, shown in FIG. 3 as a "Voice on LAN" or system configured for a telephony-based application. Such TSAPI-compliant and TAPI-enabled systems will facilitate full-featured telephony at the computing device. (According to any particularly

preferred embodiment, such systems could be implemented through one or more software programs installed on or with hardware systems or devices.) Other IPS clients 156 may be accessed via command bar 150. Various  
5 environmental controls 160 (e.g. any type of "intelligent appliance" or like device, including but not limited to those devices shown in FIG. 3) may be accessed via command bar 150 through an environment object 158. Command bar 150 further includes access to a white board  
10 162 (e.g., a recordable presentation device) and various interfacing objects via "Netmeeting" object 164 (e.g., an application program allowing on-line communication by two or more persons who virtually attend a netmeeting via their respective computing devices). FIG. 3 also  
15 indicates where each of the objects and/or applications resides (e.g., Windows applications 166, objects local to the device 168, Windows API communication 170, etc.).

Referring now to FIGS. 4A-T, FIGS. 4A-T are user interface screens for interface with a worker via a  
20 portable computing device according to an exemplary embodiment of the present invention which is implemented using a Microsoft Windows 95™ operating system. These screens differ slightly from those available in the embodiment of FIG. 3 and, thus, serve as a second  
25 exemplary embodiment of the types of application options available to the worker. Applications accessible to the user may fall under one of five categories: telephony, messaging, collaboration, internet and environment. Each category has associated with it several user interface  
30 screens, and each screen has various options to allow the user to engage different applications, according to privileges accorded to and/or preferences selected by the user.

FIG. 4A is a user interface screen for  
35 interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including telephony/monitor applications. The

screen may include a keypad and various telephony options, e.g. hold, conference call, forward call, etc.

FIG. 4B is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including telephony/speed dial applications. The screen may include icons and/or text indicating selected numbers most frequently called.

FIG. 4C is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including messaging/voice applications. The screen may include voice message playback controls such as rewind and save, and a voice message listing.

FIG. 4D is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including messaging/e-mail applications. The screen may include folders for organizing e-mails and an e-mail message listing.

FIG. 4E is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including messaging/paging applications. The screen may include pager tools, such as "send", and a pager message listing.

FIG. 4F is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including collaboration/connection applications. The screen may include a conference room listing or other users connected to the system.

FIG. 4G is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including collaboration and sharing applications. The screen may include a list of file folders and/or files available to one or more users.

FIG. 4H is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including collaboration/video applications. The screen may include a screen identifying the video clip and a video viewing screen; control over the video image (e.g. zooming, resolution, etc.) may be provided.

FIG. 4I is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including collaboration/file sharing in the manner of file transfer capability, enabling the user to send or receive files to other users and/or locations.

FIG. 4J is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including collaboration/chat applications. The screen may include a screen identifying the parties involved in the chat and a text box for displaying chat messages.

FIG. 4K is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including collaboration/whiteboard applications. The screen may include various controls for a whiteboard such as "Next Page" and "Record" and a whiteboard.

FIG. 4L is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including internet/favorite sites applications. The screen may include a selection of internet interface applications and a list of favorite sites for each application.

FIG. 4M is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including internet/history applications. The

screen may include a display documenting the history of sites visited or related information.

FIG. 4N is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including internet/newsgroup applications. The screen may include a listing of newsgroups, if any, selected by or for the user as well as particular articles or threads within the newsgroup.

FIG. 4O is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including environment/projectors applications. The screen may include various settings for audio and video projections.

FIG. 4P is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including environment/screens applications. The screen may include controls for one or more viewing screens at the location.

FIG. 4Q is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including environment/lighting applications. The screen may include controls for one or more lighting sources at the location.

FIG. 4R is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including environment/blinds applications. The screen may include controls for one or more sets of window blinds or shades.

FIG. 4S is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including environment/VCR applications. The

screen may include a variety of controls for one or more video cassette recorders (VCR).

FIG. 4T is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including environment/HVAC applications. The screen may include controls for a variety of heating, ventilating, and air conditioning operations.

FIG. 4U is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including environment/display applications. The screen may include controls for one or more displays, including selectable switching for the display input from various sources (e.g. video input, document camera, computer monitor input).

FIG. 4V is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including collaboration/persistence applications. The user input screen may include controls for a variety of display output devices (e.g. video destinations) as may be present in the graphics display system in a work space and associated video input devices (e.g. video sources). As shown, the work space includes six LCD displays, two plasma displays and a backlit "softboard" (e.g. recordable whiteboard) display, each of which may be visible to one or more persons present in the work space, to hold video display information. Video input devices may include one or more "softboards" (e.g. recordable whiteboards), or local input from the computing device. The display of video input on each of the video output devices may be controlled by a "drag and drop" type of graphical user interface (which also provides for erasing of each video output device).

FIG. 4W is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present

invention including collaboration/video applications. The screen may include controls for a video display (e.g. video conferencing), including screen adjustments, channel selection, input selection, and audio control.

5           FIG. 4X is a user interface screen for interface with a worker via a portable computing device according to an exemplary embodiment of the present invention including internet/browser applications. The screen may allow the selection and viewing of an internet  
10       web site and/or other similar document format (e.g. HTML). The user interface may allow for user commands similar to any typical "web browser" (such as Netscape Navigator version 4.04 or Microsoft Internet Explorer version 4.0), as related to loading and viewing web pages  
15       or similar documents.

As will be apparent to those of skill in the art who review this disclosure, according to alternative embodiments, a wide variety of other applications are possible according to various alternative embodiments.  
20       Moreover, other user interface screens can be provided suitable for each application so that a worker is given capability and/or control over the application. As a result, access to and/or control of a wide variety of systems, devices, equipment and appliances is available  
25       to a user through the command bar at the user interface screen.

According to a particularly preferred embodiment, the user interface screens (i.e. within the "command bar") are dynamically reconfigurable according  
30       to the actual privileges and specific preferences of the worker, as well as the presence of "intelligent appliances" corresponding to the IPS and to the user's specific location. For example, each user interface screen will only display the capability, information  
35       and/or controls that the worker is entitled to have (or will only appear if the user is entitled to the capability) based on the association provided through the IPS/NPA.



5

Although the foregoing description has been provided for the presently preferred embodiment of the invention, the invention is not intended to be limited to any particular arrangement, but is defined by the appended claims. These and other alternative configurations of the invention, that may occur to those skilled in the art, are intended to form a part of the invention to the extent such alternatives fall within the scope of the appended claims.

## CLAIMS

1. A method of supporting a worker using a computing device in a distributed work environment, the distributed work environment including a plurality of physical locations and a plurality of network access stations associated with the plurality of physical locations, the network access stations being in communication with a network such that the computing device is connectable to the network via one of the network access stations, the method comprising:

establishing a network connection between the computing device and the network via one of the plurality of network access stations;

communicating to the network a unique station identifier associated with the network access station;

determining the physical location of the worker associated with the computing device based on the unique station identifier; and

providing the worker associated with the computing device with privileges associated with the physical location.

2. The method as recited in claim 1, further comprising communicating to the network a unique device identifier associated with the computing device, wherein the provided privileges are further based on the unique device identifier.

3. The method as recited in claim 2, wherein the unique device identifier includes data representative of an identify of the worker associated with the computing device, and the provided privileges are further based on the identity.

4. The method as recited in any preceding claim, further comprising:

determining an identify of the worker associated with the computing device; and

5 providing the worker with privileges associated within the identity.

5. The method as recited in any preceding claim, wherein providing the worker with privileges associated with the physical location includes providing the worker with telephony services at the physical location.

6. The method as recited in claim 4, wherein providing the worker with privileges associated with the identity of the worker includes providing the worker with privileges according to preferences indicated by the worker.

7. The method as recited in claim 4, wherein providing the worker with privileges associated with the identity of the worker includes associating the worker with telephony services according to preferences indicated by the worker.

8. The method as recited in claim 7, wherein providing the worker with privileges associated with the physical location includes associating the worker with telephony services at the physical location.

9. The method as recited in any preceding claim, wherein providing the worker with privileges associated with the physical location includes enabling network services including

access to network devices within the distributed work environment.

10. The method as recited in any preceding claim, further  
5 comprising modifying privileges and/or preferences associated with the identity of the worker.

11. The method as recited in any preceding claim, wherein  
10 establishing the network connection includes establishing an infrared data link between the computing device and the network access station.

12. A method of providing a worker using a computing device with privileges and services associated with a physical location  
15 in a distributed work environment, the physical location having a network access station associated therewith to provide a network connection between the computing device and a network, the method comprising:

20 establishing a network connection between the computing device and the network;  
providing to the network a unique device identifier associated with the computing device and a unique station identifier associated with the network access station;  
searching a database to determine whether the unique  
25 identifier is registered in the database;  
if the unique device identifier is registered, associating the computing device with the unique station identifier;  
if the unique device identifier is not registered, registering the unique device identifier and associating  
30 the computing device with the unique station identifier;  
and

providing the worker with privileges and services available over the network and/or other systems based on the association between the unique device identifier and the unique station identifier.

5

13. The method as recited in claim 12, wherein the unique device identifier includes data representative of an identity of the worker associated with the computing device and the provided privileges and services are further based on the identity.

10

14. The method as recited in claim 13 or claim 14, wherein the provided privileges and services are provided in accordance with preferences associated with the identity of the worker.

15 15. The method as recited in claim 14, wherein the preferences include environmental system settings.

16. The method as recited in any one of claims 12 to 15, wherein providing the worker with privileges and services includes routing telephone calls intended for the worker to a selected telephone set and/or directly to the computing device.

17. The method as recited in any one of claims 12 to 16, wherein providing the worker with privileges and services includes enabling the worker to control environmental systems including lighting, HVAC and appliance settings associated with the physical location.

18. An infrared data communications system for supporting a worker using a computing device in a distributed work environment with a plurality of physical locations having a

plurality of network access stations connected to a network so that the computing device is connectable to the network at a network access station associated with a physical location within the work environment which comprises:

- 5        means for providing to the network a network physical address associated with the network access station;
- means for determining an identity of the worker associated with the computing device;
- means for determining the physical location of the worker associated with the computing device;
- 10       means for providing the worker associated with the computing device with privileges and services associated with the physical location; and
- means for providing the worker associated with the computing device with privileges and services associated with the identity of the worker.
- 15

19. The infrared data communications system as recited in claim 18, further comprising means for modifying the privileges and services associated with the physical location of the network physical address.

20

20. The infrared data communications system as recited in claim 18 or claim 19, further comprising means for modifying the privileges and services associated with the identity of the worker.

25

21. The infrared data communications system as recited in any one of claims 18 to 20, further comprising a reconfigurable database for maintaining the privileges and services associated

30

with the physical location and the privileges and services associated with the identity of the worker.

22. In an infrared data communication system for supporting a  
5 worker using a computing device in a distributed work  
environment having a plurality of physical locations having a  
plurality of network access stations connected to a network so  
that the computing device is connectable to the network at a  
network access station associated with a physical location  
10 within the work environment, an improvement comprising each  
network access station having a unique network physical address  
associated with a physical location within the work environment  
so that, when the computing device is connected to the network,  
the network physical address is provided to a network database  
15 and the worker is provided access to privileges and services  
associated with the physical location.

23. In the infrared data communications system of claim 22,  
the improvement further comprising an article of furniture,  
20 wherein at least a portion of the network access station is  
attached to the article of furniture.

24. In the infrared data communications system of claim 22 or  
claim 23, the improvement further comprising the computing  
25 device having an infrared port and the network access station  
having an infrared transceiver so that an infrared data link  
that is established between the infrared port of the computing  
device and the infrared transceiver of the network access  
station.

30

25. In the infrared data communications system of any one of claims 22 to 24, the improvement further comprising the network database including a registry of services available at the physical location associated with the network access station and  
5 of preferences associated with the worker.

26. An infrared communications system for supporting a worker having an identity at a computing device in a distributed work environment with a plurality of physical locations having a  
10 plurality of network access stations connected over an infrared data link to a network so that the computing device is connectable to the network at a network access station associated with a physical location within the work environment, which comprises:

15 a location/association system coupled to the network and configured to initiate an association process when the computing device is connected to the network at a network access station and to establish privileges and services for the worker upon completion of the association process;  
20 a physical location database managed by the location/association system and provided with available services associated with the physical location of each network access station according to a unique network physical address associated with the network access  
25 station;  
a worker preference database managed by the location/association system and provided with privileges and preferences associated with the identify of worker;  
so that when the computing device of the worker is  
30 connected to the network at the network access station at the physical location the worker is provided with



privileges and services according to the physical location and/or the identity of the worker and with preferences according to the identity of the worker.

5 27. The infrared data communications system as recited in claim 26, wherein at least one of the plurality of network access stations is associated with an article of furniture.

10 28. The infrared data communications system as recited in claims 26 or claim 27, wherein the available privileges and services at the physical location include telephony services and access to network devices.

15 29. The infrared data communications system as recited in any one of claims 26 to 28, wherein the available privileges and services at the physical location include environmental control including lighting, HVAC and appliance settings.

20 30. The infrared data communications system as recited in any one of claims 26 to 29, wherein the privileges and services of the worker include telephony and network computing privileges and services.

25 31. The infrared data communications system as recited in claim 30, wherein the telephony privileges and services include the routing of telephone calls to the nearest telephone set and/or directly to the computing device.

30 32. The infrared data communications system as recited in claim 30, wherein the network comprising privileges and services

include electronic mail, peripheral connections, application programs and database access through the computing device.

33. The infrared data communications system as recited in  
5 claim 27, wherein the article of furniture provides a  
worksurface and the computing device is a portable computer  
placed on the worksurface.

34. The infrared data communications system as recited in any  
10 one of claims 26 to 33, wherein each of the plurality of network  
access station is configured to be installed within an article  
of furniture.

35. The infrared data communications systems as recited in any  
15 one of claims 26 to 34, further comprising a reconfigurable  
database for maintaining the privileges and services associated  
with the physical location and the privileges and services  
associated with the identity of the worker.

20 36. A method of supporting a worker using a computing device  
in a distributed work environment substantially as described  
herein with reference to the accompanying drawings.

37. A data communications system substantially as described  
25 herein.



Application No: GB 9911511.5  
Claims searched: 1-37

Examiner: Ben Micklewright  
Date of search: 20 January 2000

**Patents Act 1977**  
**Search Report under Section 17**

**Databases searched:**

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK Cl (Ed.R): G4A (AAP AFL)

Int Cl (Ed.7): G06F (1/00 17/60) H04L (9/32 12/24)

Other: Online: WPI, EPODOC, PAJ, INSPEC, COMPUTER

**Documents considered to be relevant:**

Category	Identity of document and relevant passage	Relevant to claims
Y	GB2296584 A (MOTOROLA) See e.g. apges 12-14 and figure 11	5-10,15-17,28-32
X,Y	WO93/21581 A3 (SECURE)	1-4,9,12-14 Y: 5-10,16
X,Y	US5479408 (WILL) See e.g. columns 4-6, column 16 lines 19-33, and column 19 lines 25-40	X: 1-14,16,18-22,24-26,28,30-32,35 Y: 15,17,29
X,Y	Infoworld, v14, n21, page 45, 25 May 1992, "Wireless badge nets advance ubiquitous computing", R M Metcalfe	X: 1-5,10-14,18-22,24-26,35 Y: 6-9,15-17,28-32

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.

**THIS PAGE BLANK (USPTO)**